

## **Listing of Claims**

This listing of claims replaces all prior listings of the claims.

1. (Currently amended) A connector for mechanically connecting hollow structures, in particular small vessels, comprising:

an annular member of deformable material, said annular member ~~having a center line and a main plane, and being~~ permanently deformable by expansion via plastic deformation from a first size in a starting position in which the connector is delivered to a desired anastomosis site, to an annular member having a second, larger size in a joining position in which the connector connects the hollow structures,

joining elements circumferentially spaced about said annular member for joining abutting walls of the hollow structures together, said joining elements comprising staple-like elements which are permanently deformable from a starting position in which the connector is delivered to a desired anastomosis site, to a joining position in which said staple-like elements engage the hollow structures to thereby cause the connector to connect the hollow structures, each said staple-like element being attached to the annular member, and comprising at least two staple portions extending from said location of said attachment between each said staple-like element and said annular member to free ends of each said staple portion, at least part of each said staple portion being tapered in a direction corresponding to a direction from the location of attachment between each said staple-like element and said annular member towards the free end of said staple portion.

2. (Previously presented) The connector as claimed in claim 1, wherein each said staple portion tapers to at least a lesser radial thickness.

3. (Original) The connector as claimed in claim 1, wherein a center line of each of the staple-like elements is disposed substantially within a radial plane of the annular member.

4. (Original) The connector as claimed in claim 2, wherein the staple-like elements are substantially straight in their starting position.

5. (Previously presented) The connector as claimed in claim 3, wherein the staple portions of the staple-like elements have extreme tips which, in the starting position, are curved to approximate an anticipated curve of said tips resulting from deformation of said staple-like elements from the starting position to the joining position.

6. (Original) The connector as claimed in claim 1, wherein the connector is made from one piece of material.

7. (Previously presented) The connector as claimed in claim 1, wherein the staple portions of at least some of the staple-like elements are configured differently on opposite sides of the point of attachment between the staple-like elements and the annular member.

8. (Previously presented) The connector as claimed in claim 1, wherein the annular member is made from a continuous, elongate piece of material having a sinusoidal pattern meandering about a circumferential line through the main plane of the annular member.

9. (Previously presented) The connector as claimed in claim 8, wherein each said staple-like element is located at an apex of the sinusoidal pattern.

10-36. (Canceled)

37. (Currently amended) A connector for mechanically connecting hollow structures, in particular small vessels, comprising:

an annular or tubular member of deformable material, said annular member having a center line, and said annular member being adapted to be permanently deformed from a first size in a starting position in which the connector is delivered to a desired site, to an annular member having a second, larger size in a joining position in which the connector connects the hollow structures,

joining elements circumferentially spaced about said annular or tubular member for joining abutting walls of the hollow structures together, said joining elements including staple-like elements which are permanently deformable by plastic deformation from a starting position in which the connector is delivered to a desired site, to a joining position in which said staple-like elements engage the hollow structures to thereby cause the connector to connect the hollow structures, each said staple-like element being attached to the annular member proximate to a center of said staple-like element and extending in a direction substantially parallel to the center line of the annular member when said connector is in said starting position, and wherein pairs of said staple-like elements are aligned with one another on said annular member.

38-39. (Canceled)

40. (Previously presented) The connector as claimed in claim 1, wherein said tapering of at least one said staple portion provides predetermined bending characteristics to said at least one staple portion.

41. (Previously presented) The connector as claimed in claim 40, wherein said tapering of said at least one staple portion causes said at least one staple portion to permanently deform to a C-shape in said joining position.

42. (Previously presented) The connector as claimed in claim 40, wherein said tapering of said at least one staple portion causes said at least one staple portion to permanently deform to a C-shape forming a circle in said joining position.

43. (Previously presented) The connector as claimed in claim 40, wherein said tapering of said at least one staple portion causes said at least one staple portion to permanently deform to a C-shape forming overlapping circles in said joining position.

44. (Previously presented) The connector as claimed in claim 40, wherein said tapering of said at least one staple portion causes said at least one staple portion to permanently deform to a B-shape in said joining position.

45. (Previously presented) The connector as claimed in claim 40, wherein said tapering of said at least one staple portion causes said at least one staple portion to permanently deform to an overlapping B-shape in said joining position.

46. (Previously presented) The connector as claimed in claim 1, wherein the tapering of said staple portions is located on a radially outer side of said staple portions.

47. (Previously presented) The connector as claimed in claim 1, wherein the tapering of each said staple portion results in a reduction of a radial thickness of a part of said staple portion, relative to a radial thickness of another part of said staple portion.

48. (Previously presented) The connector as claimed in claim 1, wherein the tapering of each said staple portion results in a reduction of a circumferential width of a part of said staple portion, relative to a circumferential width of another part of said staple portion.

49. (Previously presented) The connector as claimed in claim 1, wherein the tapering of each said staple portion results in a reduction of both a radial thickness and a circumferential width of a part of said staple portion, relative to a radial thickness and a circumferential width, respectively, of another part of said staple portion.

50. (Currently amended) The connector as claimed in claim 6, wherein a laser ~~is~~is employed to make the connector.

51. (Previously presented) The connector as claimed in claim 6, wherein electric erosion is employed to make the connector.

52. (Previously presented) The connector as claimed in claim 6, wherein the connector is fabricated by first making a two-dimensional shape from the single material, and then forcing the two-dimensional shape into a desired three-dimensional shape.

53. (Previously presented) The connector as claimed in claim 52, wherein the two-dimensional shape is made by photo-etching.

54. (Previously presented) The connector as claimed in claim 52, wherein the two-dimensional shape is made by electroplating.

55. (Previously presented) The connector as claimed in claim 6, wherein the connector is fabricated by first making a two-dimensional shape from the single material, and then bending and welding portions of the two-dimensional shape to create a desired three-dimensional shape.

56. (Previously presented) The connector as claimed in claim 55, wherein the two-dimensional shape is made by photo-etching.

57. (Previously presented) The connector as claimed in claim 55, wherein the two-dimensional shape is made by electroplating.

58-64. (Canceled)

65. (New) The connector as claimed in claim 1, wherein each said staple portion is tapered from a position proximate the annular member.